

4	3	2	1
---	---	---	---

D	<u>FILE NAME</u> P180V124.hex	<u>SIZE</u> 28577 B	LTR. A	REVISIONS		DATE 8/27/10	APPR. JDG3	D
				DESCRIPTION				
				RELEASED, VERSION 1.0 REVISED PER ECO E16574 VER 1.24				

C								C

B								B

A	<u>UNLESS OTHERWISE SPECIFIED</u>			DRAWN	JRY	1/31/08	<div style="font-size: 2em; font-weight: bold; letter-spacing: 0.5em;">R A V E N</div>	INDUSTRIES, INC SIOUX FALLS, SOUTH DAKOTA		A
	DIMENSIONS ARE IN INCHES ONE PLACE DECIMALS ±.06 TWO PLACE DECIMALS ±.03 THREE PLACE DECIMALS ±.010 FRACTIONS ± 1/16 ANGLES ± 0°-30° BREAK EDGES .005-.015			CHECKED						
				PROJ. ENG.	JDG	3/26/08				
	MATERIAL			DATE STAMP			TITLE SOFTWARE SPECIFICATIONS, NODE, CAN, ACCUROW			
	FINISH			RELEASE FOR PRODUCTION			CODE IDENT. NO.	SIZE	DRAWING NUMBER	
							14979	A	077-0159-180	
	DO NOT SCALE DRAWING			NUMBER	APPROVED	DATE	SCALE	NA	SHEET 1 OF 2	
				E12856	JDG	3/26/08				

4	3	2	1
---	---	---	---

AccuRow Node Firmware Release Notes

Version: 1.24

1. Modified so the heartbeat from the console is not required to increment to fix issues with multiple consoles on the CAN bus.
2. Fixed bug so that boom outputs would not be grounded after power drop.
3. Added switch de-bounce so implement switch will not turn off/on intermittently.

Version: 1.10

1. Updated to improve CAN communications with CAN field computer.
2. Reinitialized CAN upon power drop.

Version: 1.00

1. Original release software.

CODE IDENT. NO.	SIZE	DRAWING NUMBER
14979	A	077-0159-180
SCALE	NA	SHEET 2 OF 2